

# Four DisplayPort 1.2 output card for LivePremier™ series

Ref. ACC-AQL-OUT-DP



**ANALOG WAY**<sup>®</sup>  
Pioneer in Analog, Leader in Digital

## Field swappable output card for LivePremier™ series with four DP 1.2 ports



4K60  
4:4:4

DP  
1.2

HDCP  
2.2

HDR

HFR  
up to  
144Hz

### Overview

The Analog Way **ACC-AQL-OUT-DP** is a field swappable output card with four DisplayPort 1.2 ports and designed to work with any **LivePremier™** live presentation switcher. Each output port supports resolutions up to 4K60 4:4:4 as well as custom resolutions such as 8192×1080@60Hz. The card supports up to 8 embedded audio channels per output and features advanced HDCP 1.4 and 2.2 handshake.

### Key features

- ▶ Four DisplayPort 1.2 output ports
- ▶ Field swappable card (not hot swappable)
- ▶ True 4K60 4:4:4 performance on every output port
- ▶ Supports 4K60 output as single, double or quad ports
- ▶ Connector status LEDs for easy troubleshooting
- ▶ HDR compliant with HDR10 and HLG
- ▶ High Frame Rate up to 144hz
- ▶ Supports up to 8 embedded audio channels per output (PCM)
- ▶ EDID management

### Technical Specifications

Four DisplayPort 1.2 output ports

Up to 21.6 Gbps bandwidth per port

10-bit formats up to:

- 4K60 4:4:4
- 4K30 4:4:4

High Frame Rate up to 2560x1440@144Hz 4:4:4 8bits

Extra-wide custom formats such as 8192×1080@60Hz (8k x 1k) or 1080×8192@60Hz

Compliant with HDCP 1.4 and HDCP 2.2

Supports BT.709 and BT.2020 color spaces

#### Dimensions

- ▶ W 5.10" x H 1.66" x D 5.80"
- ▶ L 129.7 mm x H 42.3 mm x P 147.4 mm

#### Weight without accessories

- ▶ 0.2 kg / 0.44 lbs

#### Shipping weight accessories included

- ▶ 0.4 kg / 0.88 lbs

#### Operating conditions

- ▶ Temperature: 0 to 40°C (32 to 104°F)

#### Warranty

- ▶ 1-year warranty on parts and labor back to factory
- ▶ Broken connectors are not covered by warranty

#### Power supply

- ▶ Powered from LivePremier™ switcher

#### Safety Compliance

- ▶ IEC/UL/EN 62368-1
- ▶ CSA22.2#62368-1
- ▶ (UL Listed E359143)